


DNA

PRODUCTS



RollSpeed High-Speed Door Brochure





The DNA Products RollSpeed High-Speed Door has been specially designed for the agri-food industry, due to its anodized aluminium finish and the use of anticorrosive, washable, and hygienic components. It is a fast action High-Speed door engineered to operate intensively at high frequency, many times a day.

The curtain is rolled up around an aluminium shaft, travelling over high-quality bearings, with the aim of reducing wear and tear and increasing durability.

These High-Speed doors are mainly used internally but can be supplied with reinforced wind bars for smaller external openings. Rapid access into your rooms can help optimise the flow of traffic.

The RollSpeed is a reliable High-Speed door with an auto close feature. Once the door is opened a timer will begin, closing the door at the time specified by the client. This can be set to close immediately after a pedestrian or vehicle has cleared the opening. Fast opening and closing times can help maintain the temperature in any controlled environments as well as reducing your energy cost.

Maximum safety is guaranteed by the Light Curtain safety system which is integrated in the guides. This protects the entire passage surface. Additionally, in case of impact, the door curtain can be easily repositioned thanks to the use of standard flexible reinforcements. More care is required if the strengthened reinforcing bars have been used in pressurised areas.

All doors are supplied with a crank handle for use in case of a power cut. A stop is activated for safety purposes, so the door cannot be used while the handle is in place.

Our High-Speed doors combine years of research and development with high quality materials to ensure low maintenance requirements and the best result for you. Due to its self-supporting structure, preinstalled components (safety cells, motor, curtain) and easily programmable control panel the RollSpeed is easy to assemble, install & maintain. They are also incredibly user friendly.

Maintenance advice is available over the phone and in many cases can prevent the need for a call-out charge as the onsite technicians are able to identify faults and rectify them with ease.

The RollSpeed is also available in combination with Overhead Sectional Doors or Roller Shutters.



SPECIFICATION

OPENING SPEED

0.9m/sec.

CLOSING SPEED

0.9m/sec.

MOTOR

The Motor can be supplied for left or right-hand operation depending on where the door is being installed.

SIZE

Widths from 1200mm (w) to 4000mm (w)

Heights from 2200mm (h) to 4000mm (h)

SAFETY

CE Mark in compliance with all the requirements of the European EN13241-1:2003 safety standard for preventing accidents and minimizing damage.

Emergency stops on both sides.

Active light curtain 2500mm high that stop the door from closing if a person or vehicle is detected.

POWER

As standard the Power Supply is 3 Phase 400V 16 Amp.

For an extra cost Single Phase 240V can be supplied.

CURTAIN MATERIAL

1mm Thick PVC 950g/m².

CURTAIN COLOURS

RAL 7035 Light Grey	RAL 7037 Dusty Grey	RAL 2008 Deep Orange	RAL 1021 Rap Yellow
RAL 5010 Gentian Blue	RAL 9010 Pure White	RAL 3002 Flame Red	RAL 6026 Opal Green

OPERATING TEMPERATURE

Ambient / Chill

+50°C / +3°C

OPENING DEVICE

Control Panel containing Open, Close and Emergency Stop buttons.
1no additional Push Button supplied as standard.

APPLICATION

Heavy & Light Industries
Steel and Iron Industries
Engineering Industries
Chemical Industries
Food Processing Industries
Textile Industries

DOOR MATERIALS

The Frame, Canopy and Motor Cover are made from Anodised Aluminium.
Anodising increases resistance to corrosion and wear and provides better adhesion for paint primers and glues than bare metal does.

EFFICIENCY

All High-Speed Doors will optimise logistics, eliminate draughts and heat loss and will reduce dust and noise pollution.

VISION PANELS

One row of rounded rectangular panels are supplied as standard.
370mm from ground.

Extra vision panels are available upon request.

CUSTOMISATION

Silk screen printing, digital prints and logos on curtains are available upon request.

SIGNAL OPTIONS

Safety Light
Safety Light with Sound
Traffic lights

OPENING OPTIONS

1no additional Push Button Block can be supplied if the Control Cabinet is to be fitted at high level to prevent tampering.

Induction Loop Inside/Outside – Included: 100mts flexible cable 1 mm thickness.

Pull Cord Inside/Outside Support and 5m cord included.

Remote Controls/Receivers.

OUR MOST POPULAR OPTIONS

Radars Inside/Outside



Rugged, high mount (7m) industrial door activation sensor.

IP67 with a large detection area.

Combines uni-directional detecting technology with the ability to differentiate between detecting pedestrians and vehicles.

Clearwave



FIGHTING THE SPREAD OF INFECTIONS

Hygienic, touchless, automatic door activation switch.

Detection range from 5-40 cm.

3 different faceplates included.



OPTIONS & ALTERNATIVES



BOLLARDS & POSTS

All of our doors can be supplied with protective Bollards which are the ideal solution to protect your doors from impact damage caused by forklift trucks, pallet trucks, lorries, etc.

The rounded shape and smooth surface of the Bollards allow for easier cleaning and hygiene control. All welds are tightly sealed preventing water and dirt from gathering inside.



ROLLSPEED-S

The RollSpeed is also available in Stainless Steel. This includes the full frame of the door (Legs, Canopy & Motor Cover).

Due to its Stainless-Steel structure (304L or 316L) and the use of anticorrosive and washable components, The RollSpeed-S is designed specifically for industries that require aggressive cleaning, saline environments or the fishing, meat, or dairy industry, where hygiene is essential.



ROLLSPEED-C

The insulated chill variant of the RollSpeed is especially useful in the access area to cold rooms (temperature above 2°C), where there are no tempered anterooms. It also considerably reduces the condensation on the curtain, avoiding water on the curtain and on the floor. This is important from a health and safety point of view as it can help prevent slips and falls.

— Have a Question? —

Please take your time to have a look at all our products around our website. If you have a question do not hesitate to contact us on:
01472 361 601 or sales@dna-products.co.uk

DNA


PRODUCTS

We supply, install, and maintain a wide range of products including Insulated Doors, High Speed Doors, Dock Levellers and Shelters, Coldrooms, Insulated Panels, Modular Shelving and many more. We have over a hundred years of experience in the industry between us and have worked with many different products giving us a wide range of knowledge and skills. We aim to supply a reliable service at the best possible prices.

📍 DNA Products, Unit 2 Holme Street, Grimsby, North East Lincolnshire, DN32 9AD

✉ sales@dna-products.co.uk

☎ 01472 361 601



NATIONWIDE
COVERAGE